

MINI VANDAL DOME CAMERA WITH HDMI OUTPUT



Elevate your security with our new security camera with HDMI output, featuring a 2.8mm lens and 5MP resolution for crystal-clear images. It offers flexible power options with DC 12V or PoE, while its intelligent face detection and customizable deterrence messages enhance security. With audio in/out capabilities, you can communicate seamlessly. Upgrade your surveillance and safeguard your store with confidence.



D3F28IP5MP



5MP RESOLUTION



2.8MM LENS



IR UP TO 20M



DC12V OR POE



HDMI OUTPUT



AUDIO IN/OUT



CUSTOM DETERRENCE
MESSAGE



DUSTPROOF &
WATER-RESISTANT



MICRO SD CARD SLOT
UP TO 256GB



CAMERA

| | |
|-----------------------|--|
| IP RATING | IP66 |
| FILTER | Removable IR Cut Filter |
| IMAGE SENSOR | 1/2.8" 5Mega-pixel Sony CMOS |
| PIXELS | 2688(H)*1944(V) |
| HORIZONTAL RESOLUTION | 5MP Max |
| LENS | 2.8mm Fixed |
| IR RANGE | 20 Meters |
| MIN ILLUMINATION | 0 Lux When IR ON |
| ELECTRONIC SHUTTER | NTSC:1/30-1/100,000s PAL:1/25-1/100,000s |

VIDEO & AUDIO

| | |
|--------------------------|----------------------------------|
| VIDEO COMPRESSION | H.264 / H.265 |
| TRANSMISSION STREAM RATE | Dual Stream (Code Rate:36Kb-16M) |
| FRAME RATE | 1-25fps (PAL) ,1-30fps (NTSC) |
| AUDIO COMPRESSION | G711A, G711U |
| NETWORK INTERFACE | RJ45*1 10M/100M |
| REMOTE CONTROL INTERFACE | / |
| AUDIO INTERFACE | input/output*1 |
| ALARM INTERFACE | input/output*1 |

NETWORK

| | |
|-----------------|---|
| PROTOCOL | TCP/IP, UDP, SMTP, PPPoE, DDNS, DHCP, FTP, RTSP, HTTP, IPv6 |
| NETWORK SUPPORT | ONVIF, API |
| MAXIMUM USERS | 10 |
| WEB LANGUAGE | English, Simplified Chinese, Traditional Chinese |

FUNCTION

| | |
|-------------------------|--|
| IMAGE SETTING | Contrast, Brightness, Sharpness, Saturation , WDR, 3DNR, HLC,BLC |
| STORAGE | NVR, VMS, TF Card |
| VIDEO TYPE | Manual, Timing, Motion Detection, Face Detection |
| ALARM TRIGGERS | Motion Detection, AI Face Detection |
| ALARM EVENT | Snapshot, Video, Alarm Output, Email Upload, |
| SYSTEM/EXPLORER SUPPORT | IE, Chrome, Firefox, Safari |
| GENERAL FUNCTION | Flashing, Mirror, OSD information overlay, Camera angle, Banner |

GENERAL

| | |
|-----------------------|--------------------------|
| POWER SUPPLY | DC12V±10%, POE |
| CURRENT CONSUMPTION | 770mA (Max) |
| DIMENSION | 114x81.8mm (4.49"x3.22") |
| WEIGHT | 600g |
| STORAGE TEMPERATURE | -30° ~ +60° |
| OPERATING TEMPERATURE | -30° ~ +45° |



2024 Global Surveillance Distribution, G.S.D Group and G.S.D are registered trademarks of Global Surveillance Distribution Group, Inc. in Canada and / or other countries. We reserve the right to change the design and specifications of the product Without notice and without incurring any obligation.