

MODEL #
CVT37IP5MP

Onvif® | GSI



COVERT NETWORK CAMERA



5MP
RESOLUTION



5MP Resolution

3.7MM Lens



IR Up To 20M

Covert Camera

The 5MP covert security camera combines high-definition imaging with discreet design, making it the perfect solution for professional surveillance in sensitive environments. Equipped with a 3.7mm lens, it delivers clear and detailed visuals, ensuring nothing goes unnoticed. Its built-in Power over Ethernet (PoE) support allows for simple installation with just a single cable for power and data, reducing clutter and setup time. With infrared night vision reaching up to 20 meters, this camera guarantees reliable performance day and night, capturing clear footage even in total darkness. Ideal for offices, retail spaces, or any location where discreet yet powerful monitoring is required, this covert camera offers security without compromise.





CAMERA

Effective Pixels	5MP
Main Stream	5MP (2592*1944)
Sub Stream	704*576
Frames Rates	NTSC :30fps(2560*1440)
Image Sensor	1/2.8" Sony 335 CMOS Sensor
DSP	Dual core 32-bit DSP
Min. Illumination	Color 0.001Lux@F1.2, B/W 0.0001 Lux@F1.2
Adjust Parameters	WDR,BLC,DNR,AE,AGC,D&N,Mirror,Flip,etc.

VIDEO

Compression	H.265+/H.265/H.264
Stream	Supports dual stream, AVI format
Bit Rate	SupportS 0.1M ~4Mbps bit rate adjustable
Frame Rate	Support 1~30fps adjust
Audio Compression	G.711 ACC compression
Alarm types	Motion Detection, Video Blind, Video Loss, Masking
Stream	2Stream

NETWORK

Web Browser	Supports WEB remote config (IE, Safari, Google Chrome, Firefox etc.)
Smart Phone	Mobile Remote Monitoring (iPhone, Android, Windows Mobile, BlackBerry, Symbian)
CMS Software	Uniform CMS Software (multiple devices management system)
Network	1 * RJ45,10/100M,Support RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP/SMTP
ONVIF	Support
POE	Built in

GENERAL

Language	English
IR Cut Filter	Set of double light switch IR-CUT filter
Lens	Pinhole lens 3.7mm
Infrared Luminary	48pcs IR Leds(940nm)
Illuminate Distance	20M
Connector	1*DC Connector ,1* RJ45(10/100Mbps T)
Supplied Voltage	DC12V/PoE(802.3af/820.3at)
Power Consumption	IR On: 600mA max., IR Off: Less than 200mA
Working Enviroment	-10°C~+60°C, 10%~90%
Size	120*70*46mm
Weight	0.29kg

