



FENNEC SERIES

BY
GSD GROUPMODEL #
GSD-NVRFNC4K-32NP-N

32 CHANNEL NETWORK VIDEO RECORDER

Onvif® | GSD

NDAA
Compliant

The **GSD-NVRFNC4K-32NP-N** is a next-generation 32-channel 4K Network Video Recorder engineered for high-capacity, professional-grade surveillance environments. Supporting recording up to 8MP resolution with dual 4K HDMI outputs and a dedicated HDMI spot monitor, it delivers exceptional clarity across extensive camera networks. With support for up to 32 IP cameras and an 8-bay HDD configuration up to **18TB** each, it provides substantial long-term storage for large-scale operations. ONVIF compliance ensures broad system compatibility, while P2P connectivity enables secure remote access from anywhere. This rackmount-ready NVR offers powerful performance ideal for enterprise and multi-site security applications.

**8MP
RESOLUTION**Up to 8MP
Resolution**Onvif**ONVIF Compliant
(G/S/T)**4K**2x 4K HDMI
Outputs**<••••>**

HDMI Spot Monitor

8HDD slot up to
16TBRackmount
Compatible

Alarm 16 In/ 4 Out



Up To 32 IP CMAS

AI FEATURES

- Human & Vehicle Detection
- Perimeter Intrusion Detection
- Line Crossing Detection
- License Plate Detection
- Facial Recognition
- Intrusion Detection
- Queue Length Detection
- Region Entry And Exit
- Cross-Counting
- Rare Sound Detection
- Stationary Object Detection
- Crowd Density Detection
- Heat Map
- Noise Detection
- Video Tampering



FENNEC SERIES

BY



MODEL #

GSD-NVRFNC4K-32NP-N

RECORDING BANDWIDTH

Resolution	12MP, 8MP, 5MP, 3MP, 2MP(1080P), 1.3MP(960P), 1.0MP(720P)
Input	256M
Output	128M

PERFORMANCE

SOC	NDAA
Installation Wizard	Yes
Compression	Audio: G.711A; G.711U Video: H.264/H.264+/H.265/H.265+
AI Features	Yes
Frame Rate	4K:60fps 4MP:120fps 2MP:240fps
Event	MD (Sensitivity Level 1~8) Video loss Beep, Email, Push notification to Mobile APP
Playback Function	Fast forward / backward (2x, 4x, 8x, 16x) Slow forward (1/2x, 1/4x, 1/8x, 1/16x)
Playback	Max 16CH playback

FONCTIONS IA INSTANT NOTIFICATIONS

<i>Human Detection</i>	<i>Region Exiting</i>
<i>Vehicle Detection</i>	<i>Cross-Counting</i>
<i>Perimeter Intrusion Detection</i>	<i>Rare Sound Detection</i>
<i>Line Crossing Detection</i>	<i>Stationary Object Detection</i>
<i>License Plate Detection</i>	<i>Crowd Density Detection</i>
<i>Facial Recognition</i>	<i>Heat Map</i>
<i>Intrusion Detection</i>	<i>Noise Detection</i>
<i>Region Entrance</i>	<i>Video Tampering</i>
<i>Queue Length Detection</i>	INSTANT NOTIFICATIONS
AI MAX CAPTURED QUANTITY	200,000
	AI REGISTERED QUANTITY 10,000

DOWNLOAD THE SMART GUARDIAN APP



WWW.GSDGROUPINC.COM



A CANADIAN ENTERPRISE

UI/MONITORING

Local	UI5.0
Web	IE10/11, Safari V12.1 above, Firefox V.52 above Google chrome V.57 above, Edge V.7.9 above
Mobile Viewer	SMART GUARDIAN
Push Notifications	Yes

INTERFACE

P/W Reset	Factory Reset : Press 10 seconds
VGA	1 (1024*768, 1280*720, 1280*1024, 1440*900, 1920*1080)
HDMI 1	1 (1024*768, 1280*720, 1280*1024, 1440*900, 1920*1080, 2560*1440, 3840*2160/EDID) Sync output with VGA
HDMI 2	1 (1024*768, 1280*720, 1280*1024, 1440*900, 1920*1080) Async output with HDMI 1

CONNECTIONS

Ethernet	2 RJ45 100/1000 Base-T
USB	USB2.0*1 (front) USB3.0*1+USB2.0*1 (rear)
Audio Out	1
E-SATA	1
HDD	8 SATA, each HDD up to 16TB
Line-In	1
RS485	1
Alarm Input/Out	16 in / 4 out

GENERAL

OSD Language	Multiple Languages : EN/FR/ES/DN/TC/IN/JP/KR
Dimension (WxDxH)	440*460*89mm
Input Voltage/Current	ATX 250W
Power Consumption	12W
Operating Temperature/ Humidity	Temperature : -10°C~+50°C (14°F ~ 122°F) Humidity : Less than 90%RH



FENNEC SERIES


BY



MODEL #

GSD-NVRFNC4K-32NP-N

DIMENSIONS



Length:450MM | Width:440MM | Height: 97.5MM



HDMI®
HIGH-DEFINITION MULTIMEDIA INTERFACE

COMPATIBLE HARD DRIVES



WD-HDDPURPLE-4T

UP TO 4TB HARD DRIVE



WD-HDDPURPLE-8T

UP TO 8TB PRO HARD DRIVE



WD-HDDPURPLE-12T

UP TO 12TB PRO HARD DRIVE