

MODEL #

B7Z2812AIO-5MP



FENNEC SERIES

BY
GSD
GROUP

HD ANALOG **BULLET CAMERA**

NDAA
Conforme




5MP
RESOLUTION



5MP
Resolution

2.8-12 MM
Motorized Lens



IR Up to 30M

**Built-in
Microphone**



**IP66
Dustproof
& Water-Resistant**

**TVI-CVI-
AHD-960H**

Introducing the **B7Z2812AIO-5MP** Bullet security camera, a powerful analog surveillance solution. With a highresolution 5MP sensor and a versatile 2.8-12mm motorized lens, this camera delivers clear and detailed imagery. Its infrared technology ensures visibility up to 35 meters even in low-light conditions, providing round-the-clock surveillance. With an IP66 waterproof rating, it's built to withstand outdoor environments, offering reliable protection against the elements. Invest in robust security with the B7Z2812AIO- 5MP Bullet camera for comprehensive monitoring needs.

VIDEO

| | |
|----------------------------------|--|
| Imaging Device | 1/2.7" Progressive CMOS |
| Total Pixels | 2608 (H) x 1960 (V) |
| Effective Pixels | 2608 (H) x 1960 (V) |
| Scanning System | progressive scanning |
| Min. Illumination | Color 0.04lux @ F1.6(AGC ON) ; B/W 0 lux @ IR ON |
| Max. Framerate | 5AHD/5TVI: 5MP@20fps 4AHD/4CVI/4TVI:P@25fps N@30fps 2AHD/2CVI/2TVI:P@25fps N@30fps CVBS: 960H |
| Focal Length (Zoom Ratio) | 2.8-12MM |
| Max. Aperture Ratio | F1.8-3.3 |
| Angular Field of View | H:106.6°-34.6°/V:54.4°-19.5°/D:132.9°-39.8° |
| Min. Object Distance | 1.2m(W/T) |
| Lens Type | Varifocal Lens |

LAWS AND REGULATIONS

| | |
|---------------|-------------|
| Safety | CE LVD |
| EMC | CE EMC, FCC |
| ROHS | RoHS2.0 |


OPERATIONAL

| | |
|------------------------------------|-------------------------|
| IR Distance | 35m |
| On Screen Display | English |
| Day & Night | Ext / Color / B/W |
| Backlight Compensation | Off / User BLC |
| Wide Dynamic Range | D-WDR (Off/On) |
| Digital Noise Reduction | 2D DNR |
| Gain Control | Auto |
| White balance | ATW |
| Electronic shutter speed | Auto |
| Reverse | Mirror |
| Remote Control Interface | ACP (AHD Coax Protocol) |
| Video Transmission distance | MAX 300M (RG-6) |

GENERAL

| | |
|--|-----------------------|
| Operating Temperature/ Humidity | -30°C ~ 55°C / 90% |
| Ingress Protection | IP66 |
| Input Voltage/ Current | 12V DC |
| Power Consumption | IR OFF ≤1W, IR ON ≤4W |
| Dimensions | Ø135.56x127.04mm |
| Weight | appr. 881g |
| Weight | Appr. 846g |

DIMENSIONS




COMPATIBLE ACCESSORIES

WALL MOUNT SOLUTION

Included

CORNER MOUNT SOLUTION



 **COMB6**

CORNER MOUNT BRACKET

POLE MOUNT SOLUTION



 **PMB6**

POLE MOUNT BRACKET

JUNCTION BOX



 **B6BASE1**

JUNCTION BOX

DOWNLOAD THE SMART GUARDIAN APP

