

MINI VANDAL DOME CAMERA WITH HDMI OUTPUT



5MP
RESOLUTION



2MP
Resolution

2.8MM Lens



IR Up to 20M

**Audio
In/Out**



DC12V

OR

POE



HDMI Output

**Custom
Deterrence
message**



**IP66
Dustproof
& Water-Resistant**

**Micro SD Card
Slot up to 1TB**

Elevate your security with our new security camera with HDMI output, featuring a 2.8mm lens and 2MP resolution for crystal-clear images. It offers flexible power options with DC 12V or PoE, while its intelligent face detection and customizable deterrence messages enhance security. With audio in/out capabilities, you can communicate seamlessly. Upgrade your surveillance and safeguard your store with confidence.



MINI VANDAL DOME **CAMERA**

MODEL #

D3F28IP2MP-HDMI

CAMERA

| | |
|---------------------------|--|
| Filter | Removable IR Cut Filter |
| Image Sensor | 1/2.9" 2MP Progressive Scan CMOS |
| Resolution | 1920(H)× 1080(V) |
| Lens | 2.8mm IR Lens |
| Min. Illumination | 0Lux |
| Electronic Shutter | NTSC:1/30-1/100,000s PAL:1/25-1/100,000s |
| Available IR Range | 15-20M |

VIDEO & AUDIO

| | |
|---------------------------------|----------------------------------|
| Video Compression | H.264 / H.265 |
| Transmission Stream Rate | Dual Stream (Code Rate:36Kb~16M) |
| Frame Rate | 1~25fps (PAL) ,1~30fps (NTSC) |
| Audio Compression | G711A, G711U |

EXTERNAL INTERFACE

| | |
|--------------------------|-----------------|
| HDMI 1.4 | 1080P/30FPS |
| Network Interface | RJ45*1 10M/100M |
| Audio Interface | input/output*1 |
| Alarm Interface | input/output*1 |



NETWORK

| | |
|------------------------|--|
| Protocol | IPv4, IPv6, DHCP, HTTP, Onvif, DNS, DDNS, FTP, UPNP, RTSP, SMTP, NTP |
| Network Support | ONVIF Profile S, API |
| Maximum Users | 10 |
| Web Language | English, Simplified Chinese, Traditional Chinese |

FUNCTION

| | |
|--------------------------------|--|
| Image Setting | Contrast, Brightness, Sharpness, Saturation, WDR, 3DNR, HLC, BLC |
| Storage | NVR, VMS, TF Card (MAX 1TB) |
| Video Type | Manual, Timing, Motion Detection, Alarm Video |
| Alarm Triggers | Motion Detection, Alarm |
| Alarm Event | Snapshot, Video, Alarm Output, Email Upload |
| System/explorer Support | IE, Chrome, Firefox, Safari |
| General Function | Flashing, Mirror, OSD information overlay, Camera angle |

GENERAL

| | |
|------------------------------|----------------|
| Power Supply | DC12V±10%, POE |
| Current Consumption | 570mA (MAX) |
| Dimension | Ø114× 82mm |
| Weight | 600g |
| Storage Temperature | -30° ~ +60° |
| Operating Temperature | -30° ~ +40° |
| IP Rating | IP67 |

DOWNLOAD THE OV CONNECT APP

