



FENNEC SERIES


BY  
GSD  
GROUP

MODEL #

GSD-DVRFNC5MP-16-N-AI

# 16 CHANNEL DIGITAL VIDEO RECORDER

Onvif® | GST

NDAA  
Compliant

The **GSD-DVRFNC5MP-16-N-AI** is a cost-effective 16-channel AI DVR that balances intelligent analytics with efficient system performance. It delivers features such as human and vehicle detection, facial recognition, and perimeter alerts, while supporting dual hard drives up to 18TB each. With 16 alarm inputs and 1 alarm output, 4K HDMI output, ONVIF compatibility, and P2P mobile access, this DVR is well suited for users seeking smart surveillance without high storage or bandwidth demands.

**8MP  
RESOLUTION****Onvif****4K****<⚡>**Up to 5MP  
Resolution LITEONVIF  
Encoder4K HDMI  
ResolutionAlarm  
16 In/ 1 Out2HDD  
slot up to 18TBSpot Monitor Out  
on BNCP2P Mobile  
ConnectionUp to 4 IP  
Cameras

## AI FEATURES

- Human & Vehicle Detection
- Perimeter Intrusion Detection
- Line Crossing Detection
- License Plate Detection
- Facial Recognition
- Intrusion Detection
- Queue Length Detection
- Region Entry And Exit
- Cross-Counting
- Rare Sound Detection
- Stationary Object Detection
- Crowd Density Detection
- Heat Map
- Noise Detection
- Video Tampering



FENNEC SERIES

BY



MODEL #

GSD-DVRFNC5MP-16-N-AI

**LIVE**

<b>IP Video Input</b>	4ch,(only IP up to 20ch)
<b>Composite Video Input</b>	Up to 20ch (Analog video + IP video)

**PERFORMANCE**

<b>Installation wizard</b>	Yes
<b>Compression</b>	Audio: G.711a / Video : H.264/H.265
<b>Display Resolution</b>	Analog : 5MP-Lite (3.9MP): 15fps 4MP-Lite: 30 fps 1080P/720P/960H: 30fps IP : 5MP/4MP/1080P/720P Single channel preview up to 2MP 30 fps multi-channel preview only substream
<b>Speed</b>	Main-stream Analog : 5MP-Lite:12fps (each ch) / 4MP-Lite:16fps(each ch) / 1080P:15fps(each ch) / 720P:PAL:25fps(each ch)/NTSC:30fps(each ch) IP : PAL:25fps(each ch)/NTSC: 30fps(each ch) Sub-stream Max PAL: 704*576:10fps(each ch)/ NTSC: 704*480:10fps(each ch) The sub-stream frame rate is less than the preview frame H.264 performance is about 20% lower than H.265

<b>Event</b>	MD (Sensitivity Level 1~8) Videlo loss Beep, Email, Push notification to Mobile APP
<b>Playback Function</b>	Fast forward / backward (2x, 4x, 8x,16X) Slow forward (1/2x, 1/4x, 1/8x,1/16x)
<b>Playback</b>	5MPLite: 96fps (Max 8CH playback), 4MPLite: 128fps, (Max 8CH playback) 1080P: 120fps (Max 8CH playback), 720P:240fps (Max 8CH playback)

**FONCTIONS IA INSTANT NOTIFICATIONS**

<i>Human Detection</i>	<i>Region Exiting</i>
<i>Vehicle Detection</i>	<i>Cross-Counting</i>
<i>Perimeter Intrusion Detection</i>	<i>Rare Sound Detection</i>
<i>Line Crossing Detection</i>	<i>Stationary Object Detection</i>
<i>License Plate Detection</i>	<i>Crowd Density Detection</i>
<i>Facial Recognition</i>	<i>Heat Map</i>
<i>Intrusion Detection</i>	<i>Noise Detection</i>
<i>Region Entrance</i>	<i>Video Tampering</i>
<i>Queue Length Detection</i>	<b>INSTANT NOTIFICATIONS</b>
<b>AI MAX CAPTURED QUANTITY</b>	200,000
	<b>AI REGISTERED QUANTITY</b>
	10,000

**\*THESE AI FEATURES ONLY WORK WITH IP CAMERAS, OR ANALOG CAMERAS WITH 2MP OR MORE**

**RECORDING BANDWIDTH**

<b>Inputs</b>	16Mbps ~80Mbps Analog channel and digital channel can be converted Encoding performance and decoding performance cannot be converted Total decoding performance 1080P 120fps
---------------	--

<b>Out</b>	96Mbps
<b>Analog-video-input</b>	16CH inputs

**UI/MONITORING**

<b>Local</b>	UI5.0
<b>Web</b>	IE10/11, Safari V12.1 above, Firefox V.52 above, Google chrome V.57 above Edge V.79 above
<b>Mobile Viewer</b>	SMART GUARDIAN
<b>Push Notification</b>	Yes

**INTERFACE**

<b>Voice Command</b>	Yes
<b>P/W Reset</b>	Factory Reset : Press 10 seconds
<b>BNC</b>	1 (704*576)
<b>VGA</b>	1 (1024*768, 1280*720, 1280*1024, 1440*900, 1920*1080)
<b>HDMI</b>	1 (1024*768, 1280*720, 1280*1024, 1440*900, 1920*1080, 2560*1440(2K) ,3840*2160(4K))
<b>Ethernet</b>	2 RJ45 100/1000 Base-T
<b>USB</b>	USB2.0*1 (front) USB3.0*1+ (rear)
<b>Audio</b>	16 in / 1 out (4 in / 1 out optional)
<b>E-SATA</b>	1
<b>HDD</b>	2 SATA HDD, up to 18TB
<b>RS485</b>	1
<b>Alarm Input/Out</b>	16 in / 1 out optical

**GENERAL**

<b>OSD Language</b>	Multiple Languages : EN/FR/ES/DN/TC/IN/JP/ KR
<b>Dimension (WXDXH)</b>	378*326*66mm
<b>Input Voltage/Current</b>	1HDD:DC12V/2A 2HDD:DC12V/5A
<b>Power Consumption (Excluding Hard Disk)</b>	TBD
<b>Operating Temperature/ Humidity</b>	Temperature : -10°C~+50°C (14°F ~ 122°F) Humidity : Less than 90%RH





FENNEC SERIES


BY



MODEL #

GSD-DVRFNC5MP-16-N-AI

## DIMENSIONS



Length:317.4MM | Width:378MM | Height: 50MM



**HDMI**  
HIGH-DEFINITION MULTIMEDIA INTERFACE

## COMPATIBLE ACCESSORIES



### BALUNHDA+

VIDEO/POWER/AUDIO OVER CAT5

**DISTANCE** 400+**FORMAT** PIGTAIL**DETAILS** VIDEO POWER AUDIO**PACKAGE** PAIR**TECHNO** TVI/CVI/AHD/ANALOG

**SWC5POE-GIGA**  
POE SWITCH



**SWC5POE-MAN**  
POE SWITCH



### BALUNHD

BALUNHD OVER TWISTED PAIR

**DISTANCE** 700+ FEET**FORMAT** PIGTAIL**DETAILS** 2MP/5MP/8MP**PACKAGE** PAIR**TECHNO** TVI/CVI/AHD/ANALOG

**WD PURPLE PRO**  
UP TO 2TB HARD DRIVE



**WD PURPLE PRO**  
UP TO 4TB HARD DRIVE



**WD PURPLE PRO**  
UP TO 8TB HARD DRIVE