

MODEL #

T2IP5MP28-L-N

CTAVUE® BY **GSD GROUP**

TURRET NETWORK CAMERA

Onvif® | GMST

NDAA Conforms



5MP
RESOLUTION



5MP
Resolution

2.8MM Lens



IR Up to 30M

Audio In/Out



IP67
Waterproof
& Dust-tight



Micro SD Card
Slot up to 1TB

Discover our **T2IP5MP28-L-N** turret type security camera. It offers an impressive 5 MP resolution, providing remarkably sharp video images. With its powerful infrared capability, it can capture clear images even in total darkness, with a range of up to 20 meters. The 2.8mm lens provides a wide field of view, ensuring comprehensive coverage. Operating efficiently in low-light conditions, with a lux rating of 0.002, this camera also offers the convenience of audio input and output options for enhanced surveillance. Suitable for both indoor and outdoor security applications, it ensures reliable and high-quality monitoring.

**VIDEO**

Imaging Device	1/2.7"
Effective Pixels	5MP 2880(H) x1620(V)
Scanning System	Progressive CMOS
Min. Illumination	Color 0.004lux @ F1.6(AGC ON) ; B/W 0 lux @ IR ON

LENS TYPE

Focal Length (Zoom Ratio)	2.8mm
Max. Aperture Ratio	F No. 1.6
Angular Field of View	Horizontal: 110°, Vertical: 58°, Diagonal: 133°
Min. Object Distance	1.8m

OPERATIONAL

IR Viewable Length	Up to 30m
Camera Title	Show/Hide
Day & Night	IR cut filter with auto switch (Day/Night/Auto/ Image/Schedule)
Backlight Compensation	Off/On (5 Zone)
Wide Dynamic Range	WDR
Digital Noise Reduction	3D DNR
Motion Detection	Off/On (8 Level)
Privacy Masking	Off/On (4 Zone, Rectangle)
Gain Control	Auto
White Balance	Auto/Manual
Electronic Shutter Speed	1/5 ~ 1/20000s
On-Board Storage	Micro SD slot, up to 1TB
Alarm	N/A
Audio	1 input, 1 output
Hardware Reset	Yes
Smart Features	Rare Sound Detection (SD) , Perimeter Intrusion Detection (PID), Face Detection (FD), Stationary Object Detection (SOD), Crowd Density Detection (CD), Human&Vehicle Detection (PD&VD), Line Crossing Detection (LCD), Queue Length Detection (QD), Heat Map (HM), Cross Counting (CC), License Plate Detection (LPD)

NETWORK

Ethernet	RJ45(10/100BASE-T)
Video Compression Format	H.265/H.264
Resolution	Main Stream @30fps: 5MP(2880x1620),4MP(2592x1520), 3MP(2304x1296), 1080P(1920x1080), 960P(1280x960), 720P(1280x720) Sub Stream @30fps: 720P(1280x720),VGA(640x480),QVGA(320x240) Mobile Stream @30fps: VGA(640x480), QVGA (320x240)
Video Quality Adjustment	256Kbps ~ 8Mbps
Bitrate Control Method	CBR/VBR
Streaming Capability	Triple-Stream(Main/Sub/Mobile)
Protocol	TCP/IP,HTTP,DHCP,DNS,DDNS,RTP/RTSP, SMTP,NTP,UPnP,SNMP,HTTPS,FTP
Security	IP address filter; complicated password; Authenticated username and password
Streaming Method	Unicast/Multicast
Application Programming Interface	ONVIF(Profile S/G/T)
Compatible Web Browsers	IE8,9,10,11, Safari V.11/above, Firefox V.51/ above Google chrome V.44/above
GENERAL	
Operating Conditions	-40°+60°C/less than ≤ 95% RH
Ingress Protection	IP67
Input Voltage / Current	D12V/POE(IEEE802.3af)
Power Consumption (IR OFF)	2W-3W
Power Consumption (IR ON)	4W-5.5W
Color/Material	White/Metal
Dimension (WXHxD)	Ø128.6 X98.6mm
Weight	appr. 474g




TURRET NETWORK CAMERA

MODEL #

T2IP5MP28-L-N

DIMENSIONS



COMPATIBLE ACCESSORIES

CEILING MOUNT SOLUTION



CMB6-G
CEILING MOUNT

EB3BASE4-G
PENDANT

CORNER MOUNT SOLUTION



COMB6
CORNER MOUNT BRACKET

POLE MOUNT SOLUTION



PMB6
POLE MOUNT BRACKET

WALL MOUNT SOLUTION



WMB5
WALLMOUNT BRACKET

WMB6
WALLMOUNT BRACKET

EB3BASE4-G
PENDANT

JUNCTION BOX



EB3BASE4
JUNCTION BOX

DOWNLOAD THE OV CONNECT APP

